

IMAGE



SPECIFICATION

Upholstery Available In Fabric or Leather
Available C.O.M. / C.O.L.

Required Fabric For Upholstery: 2,48 Lm / 8.14 ft
Required Leather For Upholstery: 3,58 Sq m / 38.53 ft²

Gross Weight: 20,50 Kg / 45.19 lb

Volume: 0,83 Cbm / 29.31 ft³

Box Dimensions: w 1020 x d 870 x h 940 mm / w 40.16" x d 34.25" x h 37"

1 per box

HARMONIZED SYSTEM CODE 94016100

ROUGH-IN DRAWING



STANDARD FEATURES

INNER FRAME

Shaped frame in bent rod-welded steel, drowned in cold-moulded polyurethane flexible foams.

INNER SEAT

The inner seat structure is made of stratified beech plywood, 22 mm thickness, completed with elastic belts, to obtain the best comfort.

PADDING

Cold-moulded polyurethane flexible foams, elasticity to the highest degree, non-deformability and comfort, 40 kg/m³ of density of the shell, 30 kg/m³ of density of the seat. CFC-free molded foam.

Wadding on seat 200 gr/Sq m.

BASE

Four legs base in solid walnut Canaletto or Olive Ash wood. Glides made of PTFE TEFLIFIT. Rubber base covered with PTFE. These glides guarantee softness, comfort and are able to cushion blows. Suitable for any type of floor, from parquet to tiles/marble, from linoleum to carpet.

COUNTRY OF PRODUCTION:

Italy

ENVIRONMENT:

Indoor

WARRANTY:

5 years

OTHERS

-Stitching's Are Made With Continuous Filament Polyester Thread With A Water Repellent Finish Made By Coats® Type Weaverbird™ This Type Of Lubricated Polyester (Tkt 010) Thread Make The Stitching Stronger, Resistant To The Abrasion, And Gives The Product More Tailoring Appearance. Allowing To Read The Forms And Design Of The Product

-All screws and assembly systems used in the production of Sitia's product are UNI EN ISO 9001-2000 and UNI ISO/TS 16949 process certified.

Sitia srl Copyright 2020 - all rights reserved. The described data could be modified without prior communication