

General info

DECORATIVO - Wall



Indoor wall mounted adjustable lamp with multiple sources, in-built switch and diffuse and direct light emission

Matt black varnished metal frame. Golden PVC foil shade covered with black fabric.

Ean	8021696158242
Item	NORDIK AP2
Installation	Wall
Guarantee	5 years
Gross weight	1.16 kg
Volume	0.015625 m ³

Technical info

Net weight	0.63 kg
Insulation class	I
Protection index	IP20
Compliance	-
Operating temperature	0° ~ +40 °C
Dimmer	No dimmerable, On-Off
Power output	100-240 V AC 50/60 Hz
Power supply	In-built, included
Adjustability	YES (by qualified operators only), electronic
	YES



Source info

Integrated source	Light bulb (not included), Integrated LED module
Replaceable source	YES (LED: by qualified operators only)
Power	E14/LED 1.5 (LED)W
Emission	Diffuse + Direct
Max consumption	max 1.5 (LED) W
Features LED	LED SMD BRIDGELUX
CCT	3000 K
Duration LED (t. 25°C)	20000 h
CRI	> 80
Light beam	23°
Light beam flux	55 lm
Useful light flux	45 (LED) lm
Photobiological risk	2
Standby power	< 0.50
Bulb included	LED INTEGRATO 55 (LED)Lm 3000K