



General info

DECORATIVO - Wall

Indoor wall mounted adjustable chandelier light with multiple sources, in-built switch and diffuse and direct light emission

Chrome frame. PVC foil shade covered with metallic filaments. Cut crystal pendants.

Ean	8021696068268
Item	OPERA AP3
Installation	Wall
Guarantee	5 years
Gross weight	1.97 kg
Volume	0.022048 m ³

Technical info

Net weight	1.55 kg
Insulation class	I
Protection index	IP20
Compliance	-
Operating temperature	0° ~ +40 °C
Dimmer	No dimmerable, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included
	YES (by qualified operators only), electronic
Adjustability	YES

Source info

Integrated source	Light bulb (not included), Integrated LED module
Replaceable source	YES (LED: by qualified operators only)
Power	E14/LED 1.5 (LED)W
Emission	Diffuse + Direct
Max consumption	max 1.5 (LED) W
Features LED	LED SMD
CCT	3000 K
Duration LED (t. 25°C)	15000 h
CRI	> 80
Light beam flux	55 lm
Useful light flux	45 (LED) lm
Photobiological risk	2
Standby power	< 0.50
Bulb included	LED INTEGRATO 55 (LED)Lm 3000K