

Stilt

armchair low backed

Technical Data

- Backrest - 18 mm thick particle board framework; cut foam, density of 25 kg/m³; upholstered;
- Armrests - 18 mm thick particle board framework; cut foam, density of 40 kg/m³; upholstered;
- Seat - steel framework with springs; cut foam, density of 35 kg/m³; upholstered;
- Base - 4-legged, powder coated steel; legs made of tube Ø 30 mm, wall thickness 2 mm;
- Extra charge option: mediabox M010 - USB A, C; 5V, 2x2,5 Amp;
- Extra charge option: worktop - MDF lacquered 19 mm - in frame colour; powder-coated steel;
- Castors - with brakes; Ø75 mm.



Selected configuration

SIS1

Seat fabric: Mica - 100% polyester

Seat colour: MC-18 Mint

Castors: No

Frame: Beige semi-matte RAL

608005


Footers: Grey

Side Table: No

USB: No

Plug: Europe plug

Weight: 36kg



Guarantee

.mdd products - 5 years.

Electrical components and fabric - 2 years.

Certificates



Sustainability

- Sustainable production - we are not indifferent to the environmental impact of our furniture, therefore we provide the essential information on the life cycle of Stilt seating through the Environmental Product Declaration (EPD).

Environmental Product Declaration Type III ITB No. 353/2022 SEATINGS.

- Steel profiles are powder-coated to reduce the emission of Volatile Organic Compounds.
- MDF boards used in the production of Stilt furniture are acquired from FSC/PEFC-certified producers.
- Sustainable production – we are not indifferent to the environmental impact of our furniture, therefore we provide the essential information on the life cycle of our products through the Environmental Product Declarations (EPD).

Fabric technical data

Mica



| | |
|-----------------------------------|--|
| Material | post-consumer recycled polyester 97%, polyester 3% |
| Weight | 305g/m2 |
| Abrasion resistance rub | 60,000 cycles Martindale, EN ISO 12947-2 |
| Colour fastness to light | scale 1-8, max. 8 - EN ISO 105-B02, 5-8 |
| Pilling resistance | scale 1-5, max. 5 - EN ISO 12945-2 EN ISO 12945-2, 4-5 |
| Colour fastness to rubbing | dry: 4-5, wet: 4-5, scale 1-5, max. 5 - EN ISO 105x12 |
| Flammability | CA TB 117-2013 ASTM E 84 class I BS EN 1021-1 cigarette BS EN 1021-2 Match BS 476 part 7 class I |