

# Stilt

## sofa low backed

### Technical Data

- Backrest - 18 mm thick particle board framework; cut foam, density of 25 kg/m<sup>3</sup>; upholstered;
- Armrests - 18 mm thick particle board framework; cut foam, density of 40 kg/m<sup>3</sup>; upholstered;
- Seat - steel framework with springs; cut foam, density of 35 kg/m<sup>3</sup>; upholstered;
- Base - 4-legged, powder coated steel; legs made of tube Ø 30 mm, wall thickness 2 mm;
- Extra charge option: mediabox M010 - USB A, C; 5V, 2x2,5 Amp;
- Extra charge option: worktop - MDF lacquered 19 mm - in frame colour; powder-coated steel;
- Castors - with brakes; Ø75 mm.

### Selected configuration

#### SIS2

**Frame:** Beige semi-matte RAL

608005

**Seat fabric:** Medley - 100% polyester

**Seat colour:** M-61189 Beige

**Footers:** Grey

**Table:** No

**USB:** No

**Plug:** Europe plug

**Weight:** 51.3kg



### Guarantee

.mdd products - 5 years.

Electrical components and fabric - 2 years.

### Certificates



### Sustainability

- Sustainable production - we are not indifferent to the environmental impact of our furniture, therefore we provide the essential information on the life cycle of Stilt seating through the Environmental Product Declaration (EPD). Environmental Product Declaration Type III ITB No. 353/2022 SEATINGS.
- Steel profiles are powder-coated to reduce the emission of Volatile Organic Compounds.
- MDF boards used in the production of Stilt furniture are acquired from FSC/PEFC-certified producers.

- Sustainable production – we are not indifferent to the environmental impact of our furniture, therefore we provide the essential information on the life cycle of our products through the Environmental Product Declarations (EPD).

---

## Fabric technical data

### Medley



<b>Material</b>	100% polyester
<b>Weight</b>	364g/m2 • 510g/lm
<b>Abrasion resistance rubs</b>	75,000 Martindale cycles
<b>Pilling resistance</b>	scale 1-5, max 5 • EN ISO 12945-2 4
<b>Colour fastness to light</b>	scale 1-8, max 8 • EN ISO 105 - B02 5-7
<b>Colour fastness to rubbing</b>	scale 1-5, max 5 • EN ISO 105x12 (wet/dry) 4-5/4-5
<b>Acoustic test sound absorption</b>	ISO 354
<b>Flammability</b>	BS EN 1021 - 1:2006 (cigarette), BS EN 1021 - 2:2006 California Bulletin CAL 117-E-Class 1