


## THAT'S IT

Advanced managerial armchair made of die-cast aluminium with mesh backrest. It combines a light but strong design with a high-tech look, perfect for executive spaces.



## DIMENSIONS



## THAT'S IT

### SEAT & BACK

---

Advanced managerial armchair entirely made of die-cast aluminium

The backrest is realized with a chromed or painted aluminium frame that supports two different types of mesh.

Spin 100% Trevira.

Spring 100% Polyester.



Two versions of adjustable lumbar support provided.



POLYPROPYLENE

SOFT POLYURETHAN

The seat is totally upholstered with side double stitching, made of high-density polyurethane foam thickness 5 cm.

Its frontal anatomic shape has an anti-stress function for the legs.

The seat is always equipped with sliding seat and removable.

### ARMRESTS

---

1. Fixed armrests in die-cast aluminium
2. Fixed armrests in die-cast aluminium and upholstered pad
3. 3D adjustable armrests in black polypropylene with soft polyurethane support and chromed aluminium profile



## THAT'S IT

### MECANISM

---

That's it is provided with self-weighting synchron mechanism integrated under-seat. Height-adjustment and synchron adjustment of seat/back with anti-shock system, lockable in 5 positions. All functions are integrated under-seat and can be adjusted through little levers.

Gas lift in compliance with DIN 4550 – 4<sup>th</sup> level.

### BASE

---

Two different bases available:

“LEGGERA” 5 spokes polished aluminium base on castors [d. 680 mm]

“LEGGERA” 4 spokes polished aluminium base on castors [d. 680 mm]

Standard black nylon castors diam. 65 mm.

Optional with same fastening kit diam. 11 mm:

- Black rubber castors (R06) or grey rubber castors with chromed carter (R07)
- Self-breaking black rubber castors (R06A)
- “Polo” rubber castors with central hole
- Black nylon feet (R08)

### CERTIFICATIONS

---

1. EN1335-A
2. 1IM FIRE RETARDANT
3. CAM



## THAT'S IT

### UPHOLSTERY

---

#### BIO-EXPO

##### CATEGORY 2

300 gr/mt2  
100% Propitex FR bacteriostatic  
Class 1UNI EN ISO 354:2003  
100.000 +/- 10% cycles Martindale

#### EXTREME

##### CATEGORY 2

350 gr/mtl  
100% Xtreme FR  
Class 1 , EN 1021-1/2  
100.000 +/- 10% cycles Martindale

#### LASER

##### CATEGORY 2

560 gr/mtl  
100% Polyester FR  
Class 1  
80.000+/- 10% cycles Martindale

#### ECOPELLE

##### CATEGORY 2

630 gr/mt2  
83% PVC, 17% Synthetic  
ISO 379-DIN75200-CSERF4/83 10%  
cycles Martindale

#### ERA

##### CATEGORY 3

448 gr/mtl  
100% Trevira CS  
Class 1UNI EN ISO 354:2003  
100.000 +/- 10% cycles Martindale

#### LASER PLUS

##### CATEGORY 3

630 gr/mtl  
100% Polyester FR Trevira  
Class1 , 4.000 +/- cycles Martindale

#### ECOPELLE SOUL

##### CATEGORY 3

760 gr/mt2  
Superficies 100% POLYURETHANE,  
Base Polyester 85%,17% Cotton  
EN1021-1/BS5852 PART 1  
>100.000 EN ISO 5470-2

#### MELANGE

##### CATEGORY 3

390 g/lin.m  
100% Trevira CS  
Class 1  
80.000 +/- 10% cycles Martindale

#### JET

##### CATEGORY 3

365+/- 5% g/lin.m  
100% Polyester FR  
Class 1  
80.000+/- 10% cycles Martindale

#### ECOPELLE SISTEMA PRO

##### CATEGORY 3

710 gr/mt2  
Surface 93% PVC  
Base Polyester 28%  
CLASS1  
100.000 CYCLES

#### ECOPELLE VITAX

##### CATEGORY 3

850 gr/mt2  
Surface 98% PVC 2% PU  
Base cotton 100%  
CLASS 1  
100.000 CYCLES

#### ONE RECYCLE

##### CATEGORY 3

525 gr/mt2  
100% recycled polyester  
Base cotton 100%  
CLASS 1IM  
100.000 CYCLES

#### LANA

##### CATEGORY 5

500 gr/mt2  
75% Lana, 25% polyamide  
Class 1  
100.000 cycles Martindale

#### PELLE

##### CATEGORY 5/6

620 g/lin.m  
100% Cow leather  
Class 1, EN 1021-1/2

#### PIED POULE

##### CATEGORY 6

550 g/lin.m  
66% cotton, 34% Polyester  
35.000 % cycles Martindale

#### EUROPOST 2

##### CATEGORY 6

710 g/lin.m  
63% PU, 16% CO, 21% PL  
Ini1975 CLASS1emme,UNI9175/FA  
50.000% cycles Martindale

#### PREMIUM /ELEGANCE

##### CATEGORY 7

100% First quality cow leather  
Thickness 1,2/1,4 mm  
EN1021-1/2

#### STEELCUT TRIO

##### CATEGORY 7

770 g/lin.m  
90% New wool worsted, 10% Nylon  
Class 1, EN 1021-1/2  
100.000 % cycles Martindale

#### REMIX

##### CATEGORY 7

415 g/lin.m  
90% New wool worsted, 10% Nylon  
Class 1, EN 1021-1/2  
100.000 % cycles Martindale

#### VELLUTO DECONTRACTE'

##### CATEGORY 7

590 g/lin.m  
19% CO, 61% PC,10% PL, 10%VI  
40.000 % cycles Martindale

#### MERIT

##### CATEGORY 7

500g/lin.m  
76% Polyester Recycled  
24% Polyester  
EN 1021-1/2  
85.000 % cycles Martindale

#### VELLUTO

##### CATEGORY 8

600 g/lin.m  
100.000 % PL Flame retardant

#### PELLE SOFT

##### CATEGORY 8

100% Cow leather Thickness,8-2 mm  
Aniline treatment – First quality  
EN1021-1/2

## **THAT'S IT** **USAGE AND CARE**

---

For a proper maintenance of the products and to maintain unchanged the characteristics of the materials, we recommend to follow some very simple care instructions.

### **FABRICS**

Cleaning: check the dedicated selection written on the color Swatch card. Usage: it is recommended to pay attention to the fabrics as they can be easily cut or ripped.

### **LEATHERS**

Cleaning: clean with a white wet cloth with water. We recommend to use high quality products for the cleaning of the leather and to follow carefully the instructions of the manufacturer. In doubt, try out the product on a hidden part and wait at least 24 hours for the occurrence of any problems. Usage: remember that the leather is a delicate material therefore, it is recommended to pay particular attention while using.

### **WOODS**

Cleaning: clean with a soft and wet cloth with warm water. We always recommend to dry immediately after the cleaning process. All liquids or other residue must be removed in order to avoid the absorption. Usage: wooden surfaces, being a natural material, could be affected by an alteration of the color shade during time and use. We also remind that wooden surfaces cannot bear with high temperatures if placed directly on the wooden top.

### **METALS**

Cleaning: both steel or aluminum surfaces, and painted ones, must be cleaned with a soft and wet cloth with hot water. For the most persistent stains, a small amount of liquid soap diluted in water may be used. We always recommend to dry immediately with a soft cloth or a leather one after the cleaning process. Never using cleaning products for steel, chlorine, bleach or other strong detergents. It is not recommended to use abrasive creams, score pads and abrasive sponges that can scratch the metal surfaces. Usage: pay attention to the stains of food such as coffee, coke, fruit juices that can leave indelible marks on the surface.

## **WARRANTY**

QUINTI guarantees the products will maintain their properties for 6 years from delivery, except normal usury and provided that they will be used according to the guidelines given. QUINTI will replace, free of charge, any product found non-compliant with this warranty, without incurring any other liability of sort. Components, external accessories or materials supplied by the buyer and applied to the products in order to customize them will not be supported by the guarantee. For an optimal maintenance of the products and to keep unchanged the characteristics of the materials with which they are made, some simple attentions are necessary.

---