

## IMAGE



## SPECIFICATION

Upholstery Available In Fabric or Leather  
 Available C.O.M. / C.O.L.

Required Fabric For Upholstery: 1,54 Lm / 5.05 ft  
 Required Leather For Upholstery: 2,20 Sq m / 23.68 ft<sup>2</sup>

Gross Weight: 13,10 Kg / 28.88 lb  
 Volume: 0,43 Cbm / 15.19 ft<sup>3</sup>  
 Box Dimensions w 710 x d 710 x h 860 mm / w 27.95" x d 27.95" x h 33.86"  
 1 per box  
 HARMONIZED SYSTEM CODE 94016100

## ROUGH-IN DRAWING



## STANDARD FEATURES

### INNER FRAME

Double radius stratified curved beech plywood, warm shaped, 14 mm thickness. Various wood essences are available. Foam moulded polyurethane, density 40 kg/m<sup>3</sup>.

### PADDING

Seat and backrest foam made of flexible polyurethane, crushproof, density D40/RC thickness 30 mm, rear backrest D40/RC thickness 0,5 mm. CFC-free.

### BEARING FRAME

Union of two symmetrical bended shapes in beech, 14 mm thickness, foldaway combined through special glues and through 3 steel blades fixed with special screws Wurth®.

### BASE

Four spoke swivel base made of lacquered die-cast aluminium, anti-slip glides assembled.

Available FSC® certified

### COUNTRY OF PRODUCTION:

Italy

### ENVIRONMENT:

Indoor

### WARRANTY:

5 years

## OTHERS

-Stitching's Are Made With Continuous Filament Polyester Thread With A Water Repellent Finish Made By Coats® Type Weaverbird™ This Type Of Lubricated Polyester (Tkt 010) Thread Make The Stitching Stronger, Resistant To The Abrasion, And Gives The Product More Tailoring Appearance. Allowing To Read The Forms And Design Of The Product  
 -All screws and assembly systems used in the production of Sitia's product are UNI EN ISO 9001-2000 and UNI ISO/TS 16949 process certified

Sitia srl Copyright 2020 - all rights reserved. The described data could be modified without prior communication