


IC Ceiling Wall 2 Outdoor Black

New

■ F012J00C030 - Black

Designed by Michael Anastassiades

Wall- or ceiling-mounted light fitting with diffuse light for exterior use available in two sizes. Frame in brushed stainless steel, brushed brass finish or painted opaque black or burgundy. The structure of the fitting is treated with a chemical conversion process for effective resistance to atmospheric agents. Special attention is recommended during installation and maintenance to prevent damage to the powder coating. Opalescent diffuser in shiny white translucent blown glass. The light comes with seals for IP-rated connection.




Main specifications

Mounting	Ceiling and wall surface	Autoprotected Lamp	No
Environment	Outdoor wet location		
Lamp category	LED retrofit		
Ilcos	No		
Dimmable	Yes		

Optical

Lighting Type	Direct
Lighting distribution	Symmetric
Cold Beam Lighting	No
Extreme Cut off	No



Beam Angle:	0°	
	h(m)	E(lx) D(m)
	1	86
	2	21
	3	10
	4	5
	5	0

Luminous flux luminaire
1400 lm

Electrical

Insulation class	I
Frequency (Hz)	50-60
Main Voltage (Vac)	220-240
Dimmable	Yes
Emergency Type	No

Physical

Colour	Black
Trim	No
Orientations	Fixed
Net weight (kg)	3.8
IP	65

Note

Bulb not included. LED: max 15W - E27

