



## General info

### DECORATIVO - Hanging

White or black powder painted aluminum ceiling rose and body. Opal color plastic diffuser. Integrated LED source.

|              |                          |
|--------------|--------------------------|
| Ean          | 8021696245706            |
| Item         | ORACLE D70 SQUARE BIANCO |
| Installation | Hanging                  |
| Guarantee    | 5 years                  |
| Gross weight | 4.05 kg                  |
| Volume       | 0.030672 m <sup>3</sup>  |

## Technical info

|                          |                                                                    |
|--------------------------|--------------------------------------------------------------------|
| Net weight               | 3.4 kg                                                             |
| Insulation class         | II                                                                 |
| Protection index         | IP20                                                               |
| Compliance               | -                                                                  |
| Operating temperature    | 0° ~ +40 °C K                                                      |
| Dimmer                   | No dimmerable, On-Off                                              |
| Power output             |                                                                    |
| Power supply             | Integrato, incluso<br>SI (solo personale qualificato), elettronico |
| Recessed specifications  | -                                                                  |
| Load resistance          | -                                                                  |
| Adjustability            | -                                                                  |
| Front protection index   | -                                                                  |
| Accessories not included | -                                                                  |

## Source info

|                        |                      |
|------------------------|----------------------|
| Integrated source      | Modulo LED integrato |
| Repleaceable source    | Si                   |
| Power                  | 44W                  |
| Emission               | Diretta              |
| Max consupcion         | max 43 W             |
| Features LED           | LED SMD              |
| CCT                    | 3000 K               |
| Duration LED (t. 25°c) | -                    |
| CRI                    | > 80                 |
| SDCM                   | 3                    |
| Light beam             | 115°                 |
| UGR Maximum            | -                    |
| Light beam flux        | 4200 lm              |
| Useful light flux      | 2200 lm              |
| Photobiological risk   | -                    |
| Standby power          | -                    |