

IMAGE



SPECIFICATION

Upholstery available in fabric or leather
 Available C.O.M. / C.O.L.

Required Fabric For Upholstery: 6,07 Lm / 19.91 ft
 Required Leather For Upholstery: 10,32 Sq m / 111.08 ft²

With SIDE TABLE TOP

Required Fabric For Upholstery: 4,55 Lm / 14.93 ft
 Required Leather For Upholstery: 7,74 Sq m / 83.31 ft²

Gross Weight: 81,70 Kg / 180.12 lb

Volume: 1,57 Cbm / 55.44 ft³

Box Dimensions: w 2330 x d 910 x h 735 / 91.73" x 35.83" x 28.94"
 1 per box

HARMONIZED SYSTEM CODE 94016100

ROUGH-IN DRAWING



STANDARD FEATURES

FRAME STRUCTURE

Steel frame, rectangular section 40x20 mm. Aluminium feet, conical section, h 170 mm.
 Anti-slip polyurethane rubber glides assembled, suitable for any type of flooring.

INNER FRAME

Inner structure of seat in double-panelled poplar and pine. Seat with coated rubber elastic straps.

UPHOLSTERY

Foam made of flexible crushproof polyurethane resin ELAST PERFORMANCE characterized by "smart memory", that allows the armchair to recover the initial support even after long and strong pressure. Seat and backrest padding in differentiated density polyurethane foam. Wadding on seat and backrest 200 gr/Sq m. CFC-free.

Available with SIDE TABLE TOP

Mdf painted/Oak/Walnut side table top. Available also with wireless charging and/or Versapad.

Available FSC® certified
COUNTRY OF PRODUCTION:
 Italy
ENVIRONMENT:
 Indoor
WARRANTY:
 10 years



VERSAPAD compact and versatile power system

CE

Electric Sockets 1 POWER SOCKET G (UK) + 2 USB 5V with shutters (child protection)

CABLES INCLUDED 2 meters FIXED PLATE BLACK

Rated voltage 220 - 250 V ac 50 Hz Rated current 13 A

Max.load power 2800W

Degree of protection IP 20

Body and covers Flame retardant polymer

Porte USB Ingresso tensione AC: 100 - 250 V ac 50/60 Hz

USB Charging ports Output DC - USB port 5V - 2.1A

USB Charging ports Total output power 10.5 W

CODE 060.08F.00002 - 060.08Y.00030

CUSTOM CODE 85366990

OTHERS

-Stitching's Are Made With Continuous Filament Polyester Thread With A Water Repellent Finish Made By Coats® Type Weverbird™ This Type Of Lubricated Polyester (Tkt 010) Thread Make The Stitching Stronger, Resistant To The Abrasion, And Gives The Product More Tailoring Appearance. Allowing To Read The Forms And Design Of The Product

-All screws and assembly systems used in the production of Sitia's product are UNI EN ISO 9001-2000 and UNI ISO/TS 16949 process certified

Sitia srl Copyright 2022 - all rights reserved. The described data could be modified without prior communication